


## APS 450L, Self Bunded Fuel Tank. Safe Fill Level 425 Liters



### Salient Features

- ü Tanks are fabricated from high grade mild steel
- ü All APS Bunded Tanks contain Lap-Joint double welded seams for extra strength
- ü Approved Bunded Fuel Tank, Compliant with Pollution Prevention Guidelines (PPG2/PPG26)
- ü 4 Way Fork Pockets and Lifting eyes on Two Sides are provided for easy and safe handling
- ü Frame designed for Multi Stacking for economical storage and transportation in Containers & Truck Beds
- ü Space efficient design : Can easily stack up to 2 high when full and 3 High when empty
- ü Internal Baffles included in all tanks to prevent Fuel Surge
- ü Unique Hex Corners for extra strength and Hose Openings in front to allow tank to be used when locked
- ü Bunded outer tank capacity 110% of volume and removable inner tank for maintenance and cleaning
- ü Outer Bund acting as a protective framework for extra security
- ü Two feed and Two Returns as standard Connection to multiple equipments
- ü Secure Lid with Lockable Hatch is provided on the tank
- ü Inner and Outer tanks sand blasted and primed to SA 2.5
- ü Three quotes of Paint for the Outer Tank (Epoxy zinc rich primer, Epoxy high build & Polyurethane surface)
- ü Two coats of Paint for the Inner Tank (Epoxy zinc rich primer and Polyurethane surface painting)
- ü ISO 9001 under process

### **Dimensions, Weights and other Specifications**

Tare Weight	380 Kg	Capacity in Liters	450 L
Laden Weight	765* Kg	Capacity in Gallons	99 G
Length	1,300 mm	Inner Tank Thickness	4 mm
Width	1,000 mm	Outer Bund Thickness	3 mm
Height	750 mm	Hose Pockets – 2 on each side	4
*Calculations based on safe fill level at 95% of total tank capacity and specific gravity of diesel at 0.9. Above Tank Picture is for illustration purpose only			